

Hasflex PAK Semi-Rigid Aluminium Flexible Ducting



Hasflex PAK Semi-Rigid Aluminium Flexible Ducting

Application

The HASFLEX PAK is a range of semi-rigid flexible ducting in aluminium which can be easily formed to produce bends with radii less than ½ dia. HASFLEX PAK offers extra flexibility coupled with the strength to meet the needs required for various industrial purposes as well as many HVAC applications.

Construction

HASFLEX PAK is manufactured from 99% pure aluminium strip spirally wound to produce a double overlapped crimp locked joint, which is resistant to unwinding and is pressure tight to 2500 pa.

Advantages

- Naturally retains its corrugation form and also achieves maximum distance between supports without 'sagging'.
- Supplied in standard 4 metre lengths compressed to 1 metre.
- Individually boxed.
- Strong and flexible.
- Easy to connect to circular ducting.
- No special tools required for cutting or fixing.
- The products have been successfully tested to BS476 parts 6, 7 and 8 with negligible smoke generation.



Technical data

Duct Material	99% Pure Aluminium
Diameter range (mm)	80-500
Temperature range	-30/+280
Maximum air velocity	25m/sec
Max.positive working pressure	2500 Pa
Standard length	4 metre
Compressed length	1 metre
Packing	Individually boxed
Clamping	Hasflex Lightning Band, Stainless Steel Clamps or Quick Release Clamps

Head Office Heath Mill Road, Wombourne, Wolverhampton, West Midlands WV5 8AP

Head Office 01902 895161
Wolverhampton Branch 01902 895161
Hailsham Branch 01323 847910

London Branch 020 8803 9622
Rochester Branch 01634 672730
Stoke Branch 01782 274000

Bury Branch 0161 796 8226
Nottingham Branch 0115 979 4527
Eastleigh Branch 02380 612954

sales@hotchkissairsupply.co.uk www.hotchkissairsupply.co.uk